

5000 Series - Working pressure 700 bar



- Ball locking
- Flow rate 25 l/min with Δp 5 bar

- 1 + 2 - Complete coupler • P/N 5220
- 1 - Female end piece • P/N 5221 (female 3/8 NPT)
- 2 - Male end piece • P/N 5222 (female 3/8 NPT)
- 3 - Metal protective cap for female end piece
- 4 - Metal protective cap for male end piece

3000 Series - Working pressure 700/1000 bar



- Hand screwing coupling, even at medium pressure
- Flow rate 23 l/min with Δp 4 bar

- 1 + 2 - Complete coupler • P/N 3000-3
- 1 - Female end piece • P/N 3050-3 (male 3/8 NPT)
- 2 - Male end piece • P/N 3010-3 (female 3/8 NPT)
- 3 - Metal protective cap for female end piece
- 4 - Metal protective cap for male end piece

10.115 Series - Working pressure 1000 bar



- Ball locking
- Flow rate 7 l/min with Δp 5 bar

- 1 + 2 - Standard complete coupler • P/N 115-1404/6404
- 1 - Female end piece • P/N 115-1404 (female 3/8 NPT)
- 2 - Male end piece • P/N 115-6404 (female 3/8 NPT)
- 3 - Metal protective cap for female end piece
- 4 - Metal protective cap for male end piece

Male end piece available with integrated safety valve,
P/N 115.6272 (male 1/4 BSP)

10.116 Series - Working pressure 1500 bar



- Ball locking
- Flow rate 7 l/min with Δp 5 bar

- 1 + 2 - Standard complete coupler • P/N 116-1202/6202
- 1 - Female end piece • P/N 116-1202 (female 1/4 BSP)
- 2 - Male end piece • P/N 116-6202 (female 1/4 BSP)
- 3 - Metal protective cap for male end piece
- 4 - Metal protective cap for female end piece

10.125 Series - Working pressure 2000 bar



- Ball locking
- Flow rate 7 l/min with Δp 5 bar

- 1 - 2 - Complete coupler • P/N 125-1202/6202
- 1 - Female end piece • P/N 125-1202 (female 1/4 BSP)
- 2 - Male end piece • P/N 125-6202 (female 1/4 BSP)
- 3 - Metal protective cap for female end piece
- 4 - Metal protective cap for male end piece

10.135 Series - Working pressure 3000 bar



- Ball locking
- Flow rate 7 l/min with Δp 5 bar

- 1 + 2 - Complete coupler • P/N 135-1505/6505
- 1 - Female end piece • P/N 135-1505 (female M16 x 1.5)
- 2 - Male end piece • P/N 135-6505 (female M16 x 1.5)