



## Description

Glycerine bath stainless steel pressure gauges provide a pressure indication (63mm diameter), pressure reading (100mm diameter) or a more accurate measurement (160mm diameter). The various couplings, adapters and couplers, rotary or not, can be used to fit the pressure gauges on the different hydraulic circuits.

## On request

- Other pressure range
- Pressure gauge panel mounting flange
- Pressure gauge rear connector
- More condensed graduations
- Dual pressure – load graduation for specific applications
- Protective screen

## Alternative and/or extra option

- Digital pressure gauge, digital display
- One- or two-threshold pressure switches
- 4-20mA or 0-10V pressure sensor
- Digital display with adjustable pressure thresholds

Diameter	Pressure range	Coupling	Class	Graduation
63 mm	0 - 250 bar	Male 1/4 BSP	1,6	every 10 bar
	0 - 400 bar			every 20 bar
	0 - 600 bar			every 20 bar
	0 - 1000 bar			every 20 bar
100 mm	0 - 250 bar	Male 1/2 BSP	1	every 5 bar
	0 - 400 bar			every 10 bar
	0 - 600 bar			every 10 bar
	0 - 1000 bar			every 20 bar
	0 - 1600 bar			every 50 bar
160 mm	0 - 1600 bar	M16x1.5 or 9/16UNF	1	every 50 bar
	0 - 2000 bar			every 50 bar
	0 - 2500 bar	every 50 bar		
	0 - 3000 bar	every 50 bar		
	0 - 4000 bar			every 50 bar

